



Features

- Contemporary design
- Choice of nylon or urethane wheel
- Riveted axle for positive wheel retention on all except for 50mm and 60mm nylon models

Applications

- Medical Equipment
- Utility Carts
- Furniture
- Store Fixtures
- Office Equipment

Options

Fasteners: Threaded, Top Plate, Grip Ring, Grip Neck

Brake: To order insert [-B] at the end of the Part Number. For brake model with urethane wheel insert [-BU] after model number.

Wheel Selection



Nylon Wheel (2)
Models shown in chart.



Urethane Wheel (2)
Add [-U] at end of part number or
add [-BU] for brake models.



For brake add [-B] to
end of part number.
Swivel radius for
50mm is 2-3/8",
60mm is 2-1/2",
75mm is 3-3/16",
100mm is 4-1/2",
125mm is 5-1/8".

Threaded Stem Models

Wheel Diameter	Tread Material	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
50mm	Nylon	75lb	2-1/4"	1-13/16"	PUT50__BK	507, 637, 634
	Urethane	75lb	2-1/4"	1-13/16"	PUT50__BK-U	507, 637, 634
60mm	Nylon	100lb	2-5/8"	2-1/16"	PUT60__BK	507, 637, 634
	Urethane	100lb	2-5/8"	2-1/16"	PUT60__BK-U	507, 637, 634
75mm	Nylon	165	3-1/4"	2-1/2"	PUT75__BK	507, 637, 634, 741, 748
	Urethane	165	3-1/4"	2-1/2"	PUT75__BK-U	507, 637, 634, 741, 748
100mm	Nylon	175	4-3/8"	3-5/8"	PUT100__BK	637, 634, 741, 748
	Urethane	175	4-3/8"	3-5/8"	PUT100__BK-U	637, 634, 741, 748
125mm	Nylon	180	5-7/16"	4-1/2"	PUT125__BK	741, 748
	Urethane	180	5-7/16"	4-1/2"	PUT125__BK-U	741, 748

To order include fastener code.
Example: (PUT75**507**BK).

