

# Softech Soft Tread Twin Wheel Casters


1-800-215-8220



## Grip Neck Stem Models (Black)

Wheel Diameter	Tread Material	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
<b>50mm</b>	Thermoplastic Elastomer	75	2-1/4"	1-13/16"	PSF50__BK	302
<b>60mm</b>	Thermoplastic Elastomer	100	2-5/8"	2-1/16"	PSF60__BK	302
<b>75mm</b>	Thermoplastic Elastomer	165	3-3/16"	2-1/2"	PSF75__BK	302

For brake add [-B] to end of part number. Swivel radius for 50mm is 2-3/8", 60mm is 2-1/2", 75mm is 3-3/16", 100mm is 4-1/2", 125mm is 5-1/8".



## Grip Neck Stem Models (Grey)

Wheel Diameter	Tread Material	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
<b>50mm</b>	Thermoplastic Elastomer	75	2-1/4"	1-13/16"	PSF50__GR	302
<b>60mm</b>	Thermoplastic Elastomer	100	2-5/8"	2-1/16"	PSF60__GR	302
<b>75mm</b>	Thermoplastic Elastomer	165	3-3/16"	2-1/2"	PSF75__GR	302

For brake add [-B] to end of part number. Swivel radius for 50mm is 2-3/8", 60mm is 2-1/2", 75mm is 3-3/16", 100mm is 4-1/2", 125mm is 5-1/8".

